

AFUX-HF C-PRO 1 KV

Low smoke halogen-free 1 kV installation cable



Afumex C-PRO

APPLICATION

For fixed surface and flush-mounted installations, indoors and outdoors. Especially for circumstances where it is required to have installation cables with a low emission of smoke and corrosive gases in case of fire.

RATED VOLTAGE

U₀/U = 0,6/1 kV

Declaration of Performance (DoP)

Ref. No 1002551



RoHS



IEC 60502-1

SFS 5546 (where appl.)

EN 50575:2014+A1:2016

EN 13501-6, class Cca-s1,d1,a1

IEC 60332-1-2

IEC 60332-3

IEC 61034

IEC 60754

Conductor	Copper
Conductor surface	Bare
Insulation	XLPE
Filling sheath	Halogenfree polymer
Outer sheath	Halogenfree polymer

Max. conductor temperature [°C]	90
Max. conductor temperature at short circuit [°C]	250
Permitted cable outer temperature during assembling/handling (min) [°C]	-15
Minimum permissible bending radius during laying	12x OD

FIRE PROPERTIES

Reaction-to-fire, CPR classification	Cca-s1,d1,a1
Flame retardant	In accordance with EN 13501-6
Halogen free	Yes

© Prysmian Group Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian Group.

DELIVERY INFO

Sno	PRODUCT NAME	EAN-code (GTIN)	Packaging type	Standard delivery length
0403388	AFUX-HF C-Pro 1kV 3x6 S K8/500	6410004033883	Drum	500
0403389	AFUX-HF C-Pro 1kV 3x10 S K8/400	6410004033890	Drum	400
0403391	AFUX-HF C-Pro 1kV 5x6 S K6M/200	6410004033913	Drum	200
0403390	AFUX-HF C-Pro 1kV 5x6 S K8/500	6410004033906	Drum	500
0403392	AFUX-HF C-Pro 1kV 5x10 S K8/250	6410004033920	Drum	250
0403393	AFUX-HF C-Pro 1kV 5x16 S K9/250	6410004033937	Drum	250
0403394	AFUX-HF C-Pro 1kV 5x25 S K9/250	6410004033944	Drum	250

© Prysmian Group Finland Oy. All rights reserved.

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group; any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without notice.

This specification is not contractually valid unless specifically authorised by Prysmian Group.

MECHANICAL AND ELECTRICAL DATA

Product name	Diameter over cable [mm]	Max. DC resistance, conductor (20°C) [ohm/km]	Current rating, ref. install. type E [A]	Weight [kg/km]	Min. permissible bending radius during laying [mm]
AFUX-HF C-Pro 1kV 3G6	13	3.08	56	350	130
AFUX-HF C-Pro 1kV 3G10	16	1.83	78	500	160
AFUX-HF C-Pro 1kV 5G6	15	3.08	56	500	150
AFUX-HF C-Pro 1kV 5G10	19	1.83	78	750	190
AFUX-HF C-Pro 1kV 5G16	22	1.15	104	1,100	220
AFUX-HF C-Pro 1kV 5G25	27	0.727	132	1,800	270

Current rating: installation method E (in free air), conductor max. operation temp.